



## Szybkozłączka G 3/8 (GW) (103451204) - Cejn



**Numer artykułu SKU:  
OT-CEJN002105**

Numer artykułu producenta:  
-----

Tylko na zamówienie



## OPIS PRODUKTU

Series 345 is a double shut-off series with both a valved coupling and nipple. The specially designed valve provides an extremely high rate of airflow. This series is well-suited for breathing air diving applications and for applications that demand a closed system when disconnected, such as surface air diving. Like most other CEJN breathing air couplings, Series 345 offers one-hand-operated connection, an integrated safety feature that guards against unintentional disconnection, a grip-friendly locking sleeve, and a broad connection range.

## DANE TECHNICZNE

Średnica	25,4 mm
Długość	61,5 mm
Zakres temperatury	-30 °C do +100 °C
Przyłącze	G 3/8
Przepływ powietrza	1100 l/min (38.8 CFM)
Materiał uszczelnienia	NBR
Maks. ciśnienie pracy	35 bar
Materiał szybkozłącza	mosiądz niklowany
Materiał wtyku	mosiądz niklowany
Min. ciśnienie rozrywające	140 bar
Średnica nominalna przepływu DN	6,2 mm (0,2")
Sześciokąt	22 mm

Nr kat.

OT-CEJN002105

Data wygenerowania podsumowania: 05.06.2026r, g. 18:46