

Czujnik indukcyjny, zbliżeniowy, seria BES (BES05WY) - Balluff



Numer artykułu SKU:
OC-BALLUFF001508

Numer artykułu producenta:

Tylko na zamówienie

BALLUFF

OPIS PRODUKTU

Charakterystyka

Cechy szczególne	Washdown Plus, Washdown
Wymiary	Ø 18 x 66 mm
Kształt obudowy	M18x1
Montaż	prawie równo z powierzchnią
Zasięg	0.5...8 mm
Interfejs	IO-Link 1.1
Wyjście przełączające	Przeciwtakt styk zwierny/styk rozwierny (NO/NC);PNP/NPN/Przeciwtakt styk zwierny/styk rozwierny (NO/NC)
Częstotliwość przełączania	700 Hz
Materiał obudowy	Stal nierdzewna (1.4404)
Materiał powierzchni aktywnej	PBT
Przyłącze	Złącza wtykowe, M12x1-Męski, 4-stykowe
Napięcie robocze Ub	10...30 VDC
Temperatura otoczenia	-40...85 °C
Stopień ochrony	IP68, IP69K

Secondary features for condition monitoring	Vibration monitoring, Inclination monitoring and installation aid, Internal temperature monitoring, Internal humidity detection
Secondary features	Identification, Device Discovery, Switching Profiles, Signal Quality Monitoring, External Signal Blanking, Signal Delay, Signal Speed Monitor, Switching Counter, Basic Statistics, Logic Blocks, Operating Hours Counter, Boot Cycle Counter, Voltage and Current Monitoring, Extreme Environment Status, Storage Usage Monitoring, Variant Configuration, Pin Assignment
Dopuszczenie / Zgodność	CE, UKCA, cULus, Ecolab, WEEE

DANE TECHNICZNE

Nr kat.	OC-BALLUFF001508
---------	------------------