Czujnik ultradźwiękowy do siłowników hydraulicznych o małym skoku, seria BFD (BFD0001) - Balluff



Numer artykułu SKU: OC-BALLUFF003908

Numer artykułu producenta: -----

Czas wysyłki: Do 3-5 dni

BALLUFF

OPIS PRODUKTU

Charakterystyka

Zastosowanie	Position monitoring in short stroke hydraulic cylinders
Zakres pomiarowy	0...80 mm
Maks. nieliniowość	±250 µm
Powtarzalność	± 50 µm
Maks. wytrzymałość na ściskanie	350 bar
Interfejs	IO-Link 1.1, Analogowy, napięcie/analogowy, natężenie z możliwością przełączania 4...20 mA/0...10 V
Pin 4	Push-pull Styk zwierny/rozwierny (NO/NC)
Pin 2	PNP/NPN/push-pull Styk zwierny/rozwierny (NO/NC)
Napięcie robocze Ub	10...30 VDC
Przyłącze	Przewód z łącznikiem wtykowym, M8x1-Męski, 4-stykowe, 0.3 m, TPU
Temperatura otoczenia	0...85 °C
Stopień ochrony	IP67
Dopuszczenie / Zgodność	CE, UKCA, cULus, WEEE
Secondary features for condition monitoring	Internal temperature monitoring

Secondary features	Identification, Device Discovery, Switching Profiles, Signal Quality Monitoring, Signal Delay, Switching Counter, Basic Statistics, Logic Blocks, Operating Hours Counter, Boot Cycle Counter, Voltage and Current Monitoring, Variant Configuration, Pin Assignment

DANE TECHNICZNE

Nr kat.	OC-BALLUFF003908

Data wygenerowania podsumowania: 05.11.2026r, g. 20:52